

Certificate of Product Approval

Certificate Number: 1613b

Issue: 01

Fastline Steel Services UK Ltd

Unit G1
Strawberry Lane
Willenhall
WV13 3RS



is authorised to use the LPCB mark in association with the product(s) listed in this certificate and appendix having complied with the requirements of the standard(s) detailed below:

Product

Imperium-2-358DB
security fencing system

Standard

LPS 1175: Issue 8
Requirements and testing procedures for the LPCB certification and listing of intruder resistant building components, strongpoints, security enclosures and free-standing barriers

This certificate and appendix is maintained and held in force through regular surveillance activities

Signed for BRE Global Ltd.

Chris Hunt
Verifier

6 November 2020
Date of Issue

6 November 2020
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX
T: +44 (0)333 321 8811 E: enquiries@breglobal.com

LPCB is a Registered Trademark of the Building Research Establishment Ltd.



Appendix to Certificate No: 1613b Fastline Steel Services UK Ltd

Issue: 01

Security Fencing System

Product Name	Type	Nominal Height (m)	Maximum Post Centres (m)	Gradients	Angles in Fence Line	Security Rating	LPCB Ref. No.
Imperium-2-358DB	Welded mesh fencing system	2.134 to 5.2	2.475	2.31°, 4.62°, 6.91°	90° to 270°	B3 (SR2)	1613b/01

Approved Assembly and Installation Drawings

Document Reference	Revision / Issue Date	Title / Contents
FSS-SR2-358 101	v106	Combined 358 Panel Configuration
FSS-SR2-358 102	F 01/03/20	Individual 358 Panel
FSS-SR2-358 103	F 01/03/20	Posts & Clamp Bar Specification - In Ground
FSS-SR2-358 104	F 01/03/20	Posts & Clamp Bar Specification - Base Plated
FSS-SR2-358 105	F 01/03/20	Corner Posts Specification - In Ground
FSS-SR2-358 106	F 01/03/20	Corner Posts Specification - Base Plated
FSS-SR2-358 107	F 01/03/20	General Arrangement - 2134 to 2440mmH
FSS-SR2-358 108	F 01/03/20	General Arrangement - 2700 to 3000mmH
FSS-SR2-358 109	F 01/03/20	General Arrangement - 3300 to 4200mmH
FSS-SR2-358 110	F 01/03/20	General Arrangement - 4500 to 5200mmH
FSS-SR2-358 111	F 01/03/20	General Arrangement - 2134 to 2440mmH Base Plated
FSS-SR2-358 112	F 01/03/20	General Arrangement - 2700 to 3000mmH Base Plated
FSS-SR2-358 113	F 01/03/20	General Arrangement - 3300 to 4200mmH Base Plated
FSS-SR2-358 114	F 01/03/20	General Arrangement - 4500 to 5200mmH Base Plated
FSS-SR2-358 115	F 01/03/20	Assembly Detail - Inter/End Post
FSS-SR2-358 116	F 01/03/20	Assembly Detail - Corner Post
FSS-SR2-358 116.1	F 01/03/20	Configurations - Corner Post
FSS-SR2-358 117	F 01/03/20	Detail - Base Plates
FSS-SR2-358 118	F 01/06/20	Stepped Bay Details
FSS-SR2-358 119	F 01/06/20	Optional Extension Details
FSS-SR2-358 120	F 01/08/20	Installation Guidance

This certificate and appendix is maintained and held in force through regular surveillance activities



Signed for BRE Global Ltd.

Chris Hunt
Verifier

6 November 2020
Date of Issue

6 November 2020
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX
T: +44 (0)333 321 8811 E: enquiries@breglobal.com

LPCB is a Registered Trademark of the Building Research Establishment Ltd.



Appendix to Certificate No: 1613b Fastline Steel Services UK Ltd

Issue: 01

Notes:

1. The 'angle in fence line' define the range of angles covered by the scope. These are measured between the attack face of two adjacent panels.
2. The fencing system is available in configurations to suit either surface mounting or embedded within concrete foundations placed in the ground. It is important to ensure that the local ground onto/into which the fence is installed offers compatible strength.
3. The fencing system should only be constructed and installed in accordance with the documents listed in the table titled Approved Assembly and Installation Drawings, using only appropriate components supplied by Fastline Steel Services UK Ltd.
4. The minimum height of the fencing system when installed on gradients listed above is 2.480 m.

This certificate and appendix is maintained and held in force through regular surveillance activities



Signed for BRE Global Ltd.

Chris Hunt
Verifier

6 November 2020
Date of Issue

6 November 2020
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX
T: +44 (0)333 321 8811 E: enquiries@breglobal.com

LPCB is a Registered Trademark of the Building Research Establishment Ltd.

