

Certificate of Product Approval

Certificate Number: 1613c Issue: 01



Willenhall WV13 3RS



Product

Imperium-1-868 security fencing system

Standard

LPS 1175: Issue 8

Requirements and testing procedures for the LPCB certification and listing of intruder resistant building components, strongpoints, security enclosures and free-standing barriers

This certificate and appendix is maintained and held in force through regular surveillance activities



Chris Hunt

6 November 2020

6 November 2020

Signed for BRE Global Ltd.

Date of Issue

Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX T: +44 (0)333 321 8811 E: enquiries@breglobal.com

LPCB is a Registered Trademark of the Building Research Establishment Ltd.







Appendix to Certificate No: 1613c Fastline Steel Services UK Ltd

Issue: 01

Security Fencing System

Product Name	Туре	Nominal Height (m)	Maximum Post Centres (m)	Gradients	Angles in Fence Line	Security Rating	LPCB Ref. No.
Imperium-1-868	Welded mesh fencing system	1.874 to 5.174	2.525	2.27°, 4.53°, 6.78°°	90° to 270°	A1 (SR1)	1613c/01

Approved Assembly and Installation Drawings

Document Reference	Revision / Issue Date	Title / Contents	
FSS-SR1-868 101	E 01/05/20	Panel Specification	
FSS-SR1-868 102	E 01/05/20	Posts and Clamp Bar Specification - In Ground	
FSS-SR1-868 103	E 01/05/20	Posts and Clamp Bar Specification - Base Plated	
FSS-SR1-868 104	E 01/05/20	Corner Post Specification - In Ground	
FSS-SR1-868 105	E 01/05/20	Corner Post Specification - Base Plated	
FSS-SR1-868 106	E 01/05/20	General Arrangement - 1830 to 2430mmH	
FSS-SR1-868 107	E 01/05/20	General Arrangement - 3000 to 3030mmH	
FSS-SR1-868 108	E 01/05/20	General Arrangement - 3300 to 4500mmH	
FSS-SR1-868 109	E 01/05/20	General Arrangement - 4700 to 5100mmH	
FSS-SR1-868 110	E 01/05/20	General Arrangement - 1830 to 2430mmH Base Plated	
FSS-SR1-868 111	E 01/05/20	General Arrangement - 3000 to 3030mmH Base Plated	
FSS-SR1-868 112	E 01/05/20	General Arrangement - 3300 to 4500mmH Base Plated	
FSS-SR1-868 113	E 01/05/20	General Arrangement - 4700 to 5100mmH Base Plated	
FSS-SR1-868 114	E 01/05/20	Assembly Detail - Inter/End Post	
FSS-SR1-868 115	E 01/05/20	Assembly Detail - Corner Post	
FSS-SR1-868 115.1	E 01/06/20	Configurations - Corner Post	
FSS-SR1-868 116	E 01/05/20	Detail - Base Plates	
FSS-SR1-868 117	E 01/06/20	Stepped Bay Details	
FSS-SR1-868 118	E 01/06/20	Optional Extension Details	
FSS-SR1-868 119	E 01/08/20	Installation Guidance	

This certificate and appendix is maintained and held in force through regular surveillance activities

ce by

Signed for BRE Global Ltd.

Chris Hunt Verifier 6 November 2020

6 November 2020
Date of First Issue

Date of Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX T: +44 (0)333 321 8811 E: enquiries@breglobal.com

LPCB is a Registered Trademark of the Building Research Establishment Ltd.







Appendix to Certificate No: 1613c **Fastline Steel Services UK Ltd**

Issue: 01

Notes:

- 1. The 'angle in fence line' define the range of angles covered by the scope. These are measured between the attack face of two adjacent
- 2. The fencing system is available in configurations to suit either surface mounting or embedded within concrete foundations placed in the ground. It is important to ensure that the local ground onto/into which the fence is installed offers compatible strength.
- 3. The fencing system should only be constructed and installed in accordance with the documents listed in the table titled Approved Assembly and Installation Drawings, using only appropriate components supplied by Fastline Steel Services UK Ltd.
- 4. The minimum height of the fencing system when installed on the gradients listed above is 2.274 m.

This certificate and appendix is maintained and held in force through regular surveillance activities

ce by

Chris Hunt

6 November 2020

6 November 2020

Signed for BRE Global Ltd.

Verifier

Date of Issue

Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX T: +44 (0)333 321 8811 E: enquiries@breglobal.com

LPCB is a Registered Trademark of the Building Research Establishment Ltd.



